

## CR 210s

### GENERAL DESCRIPTION

Contrabass CR 210s is a relatively small, 2x10" (254 mm) reflex-loaded subwoofer designed for low visibility. By using minimal floor space and having discreet appearance, CR 210s can be placed in a corner as a table, and it is a perfect fit for small venues, including homes and other AV applications.



The Contrabass CR 210s seamlessly combines with String or Cello series loudspeakers. ST 23, ST 43, CF 5, CC 8 and CF 10 are a perfect match for CR 210s. This unconventionally shaped neutral looking cabinet can be easily installed on ceilings, against walls, or hidden under seating or as a side table. When employed in multiples, CR 210s can cover relatively large rooms and blend in nicely with interiors. This cabinet is available in custom colours.

### FEATURES

- ✓ Compact, high-performance reflex-loaded dual 10" (254mm) Sub-woofer
- ✓ Fast, integral wall/ceiling mounting clamp
- ✓ Easy to install
- ✓ Can retrofit into existing venues
- ✓ Less than 9" tall, it can easily go under a stairway

### SYSTEM APPLICATIONS

- ✓ Restaurants
- ✓ A/V spaces, conference rooms
- ✓ Bars and lounges
- ✓ Gyms
- ✓ Homes

## SYSTEM SPECIFICATIONS

Type	Compact subwoofer
Frequency Response (1)	48 Hz-250 Hz $\pm$ 3 dB
Drivers	LF: 2x10" (254 mm) with a 2" (50 mm) voice coil
Recommended Amplifier Upto	1200 Watts
Sensitivity (1 Watt/1 metre)	97 dB
Maximum SPL (9)	121 dB continuous, 129 dB Max
Nominal Impedance	8 Ohms
Dispersion	Omni
Crossover	LPF 110Hz
Enclosure	Baltic birch ply
Finish	Textured black paint
Protective Grille	Perforated steel
Connectors	2 x Neutrik NL4
Pin Connections	Input: $\pm$ 1, Link through: $\pm$ 2
Standard Colours	Black
Fittings	Flying system, Integral feet
Dimensions - Product	(W) 811mm x (H) 272mm x (D) 510mm
Dimensions - Including packing	(W) 837mm x (H) 290mm x (D) 536mm
Horn	NA
Rated Continuous Power AES	600 Watts
Rated Maxium Power/Program Power	1200 Watts
Peak Power	2000 Watts
Net weight	28 kgs
Shipping Weight	30 kgs

Subwoofers measured on axis in half space @ 1 watt/1 meter using band limited pink noise. In the en-deavour to continuously improve the product with design refinements introduced into existing products. Any current CSC product may differ in some respect from its published description. However this will always equal or exceed the original design specifications. Every CSC product is built to the highest standards and tested to ensure that it meets the performance criteria specified.

## SAFETY INSTRUCTIONS

- ÿ When flying speakers, appropriate hardware and techniques must be employed for safely suspending the enclosures.
- ÿ Ensure all instructions that appear on specific loudspeaker datasheets are followed.
- ÿ All speaker hardware and flying apparatus must be regularly inspected for any visual or mechanical failure.
- ÿ Leave adequate distance between speakers and the audience. Refer to your local authority for Health and Safety guidance when using loudspeaker systems.
- ÿ The CSC digital controller should only be programmed by a CSC authorized technician. Do not use CSC loudspeaker systems without the correct controller and the program. If a system fails due to incorrect controller use, warranty is void.
- ÿ Protect your speakers and electronics from exposure to humidity, water or rain.
- ÿ CSC loudspeakers and electronics are covered against defects in workmanship or materials for a period of two years from the original date of purchase. The CSC warranty **does not cover** any item which in CSC's opinion has failed due to user abuse, accident, modifications.

The defective item will be repaired/replaced with no charge for materials or labour. However the item should be adequately packed and dispatched, pre-paid, to a CSC authorized distributor/service center.

