

## CSC ALL WEATHERS SPECIFICATION

MODEL NO.	CSC MI240	CSC MI290	CSC MK420	CSC MK460
DESIGN	TW	TW	TW	TW
MAXIMUM POWER HANDLING	40	60	40	
OPERATING VOLTAGE	100 V/8 OHM	100 V/8 OHM	100 V/8 OHM	100 V/8 OHM
POWER HANDLING RMS	20	30	20	30
FREQ RESPONSE	130HZ-15KHZ	120HZ-15KHZ	120HZ-16KHZ	120HZ-16KHZ
SENSITIVITY	90	91	89	102
ANGLE OF DISPERSION	90 x 40	100 x 40	360 x 100	360 x 100
INSTALL DIMENSION	NA	NA	NA	NA
DEPTH IN MM	NA	NA	NA	NA
WEIGHT	2.8 Kg	3 Kg	3.1 Kg	7 Kg
SPEAKER CABLE	WIRE UPTO 2.5 MM <sup>2</sup>	WIRE UPTO 2.5 MM <sup>2</sup>	WIRE UPTO 2.5 MM <sup>2</sup>	WIRE UPTO 2.5 MM <sup>2</sup>
COMPONENTS				
CROSS OVER FREQUENCY	4K	4K	NA	NA
CONNECTOR TYPE	PUSH FIT	PUSH FIT	WIRE	WIRE