

CSC MI 02

GENERAL DESCRIPTION



CSC MI 02 is a tiny ceiling speaker just 3" in dia powered by a 2" LF full-range driver. This full-range ceiling speaker provides clear vocal reinforcement. It is easy to install and can be used to suit the application with communication is more important than music. Featuring a powerful 2" (50 mm) transducer, it has superb Off-axis uniform coverage blending with seamless intelligibility. Excellent for voice applications, it is capable of delivering clear vocals. It can be safely used in bathrooms, kitchens, saunas, and even under outdoor eaves. Installation is easy. Cut a hole, feed the wires, and drop the speaker in.

FEATURES:

- ▶ Compact, high-performance ceiling speaker
- ▶ High power 15 Watt - maximum SPL 101 dB
- ▶ Freq response from 200 Hz –to 12 kHz
- ▶ Brilliant vocal propagation
- ▶ Very smooth off-axis response - useable out to 100° (-6 dB)
- ▶ Fast, integral hardware

SYSTEM APPLICATIONS:

- ▶ Distributed audio/ public address system
- ▶ Commercial and retail
- ▶ Can be used in high humidity areas
- ▶ Recommended for use in Hotels, shopping malls, schools,
- ▶ Hospitals and conferencing.

Specifications	CSC MI 02
Type	Ceiling Speaker open Baffle
Frequency Response	200 Hz-12 kHz \pm 3 dB
Drivers	LF: 1 x 2" (25 mm) LF full range
Sensitivity (1 Watt/1 meter)	88 dB
Maximum SPL	101 dB
Nominal Impedance	Selectable 8 Ohms or 70/100V line
Tapings	Selectable 5w/10w
Dispersion	100° from central axis
Nominal Power AES	15Watt
Maximum power/program power	30 Watt
Peak power	60 Watt
Backbox	None
Enclosure	ABS (UV stabilized)
Standard color	White
High Pass	150 HZ
Connectors	Push to fit
Pin connections	Input Red and black
Protective Grille	Perforated steel
Finish Grille	UV coated powder coated
Mounting	Butterfly locks
product Dimensions (mm)	105x70
Packing Dimensions (mm)	110x110x 80
Cut out dimensions (mm)	96
Net Weight (kgs)	.46
Shipping Weight (kgs)	.69
Packing	Single unit

Mid highs measured on-axis in full space@ 2.83V/1 meter using band-limited pink noise

We continuously improve our product's design, with re nements introduced into existing products. The current CSC product may differ in some respect from its published description. However, this will always equal or exceed the original design speci cations. Every CSC product is built to the highest standards and tested to ensure that it meets the performance criteria speci ed

SAFETY INSTRUCTIONS

- ▶ Ensure enough clear space in the false ceiling to house the speaker.
- ▶ Draw a circle of dia mentioned above. Cut a hole and drop in the ceiling speaker.
- ▶ Remove the grill from the speaker by gently pushing the mounting poles down until they ease the grill out, position the rear of the speaker facing into the hole.
- ▶ Connect the speaker to the system, ensuring all connections are correct. Connect the power to the mains and signal to the audio IN.
- ▶ Turn the butterfly knobs with the ends located over the ceiling. Tighten the screw until the speaker is clamped onto the false ceiling.
- ▶ Replace the speaker grill.
- ▶ Turn on the music source and enjoy the amazing sound of the CSC loudspeaker.

